

FLAT GROUND STOCK 100% De-Carb Free, Alloy & Tool Steels

Typical Size Tolerances

Width	(+.005"/-.000")
Thickness	(+/- .001" up to 1-1/4") (+/- .002" over 1-1/4")
Length	(+1/4"/-.000")

Lengths Available*

18" or 36" Lengths

*Please call for all special requirements.

We offer the following grades of steel in both our flat ground stock and in drill rod stock. Please contact our office for the most up-to-date stock availability.

Cougar™	Flat Ground and Drill Rod
Redstar HWD™	Flat Ground and Drill Rod
Dexite™AH	Flat Ground and Drill Rod
Dexite™ #14	Flat Ground and Drill Rod
Dexite™ Supershock	Flat Ground and Drill Rod
Sheffield™	Flat Ground Only

Widths	Thicknesses								
	1/8"	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"
1/2"	X	X	X	X	X	X	N/A	N/A	N/A
3/4"	X	X	X	X	X	X	N/A	X	X
1"	X	X	X	X	X	X	X	X	X
1-1/4"	X	X	X	X	X	X	N/A	X	X
1-1/2"	X	X	X	X	X	X	X	X	X
2"	X	X	X	X	X	X	X	X	X
2-1/2"	X	X	X	X	X	X	N/A	N/A	N/A
3"	X	X	X	X	X	X	X	X	X
4"	X	X	X	X	X	X	X	X	X
5"	X	X	X	X	X	X	N/A	N/A	N/A
6"	X	X	X	X	X	X	X	X	X
Square	N/A	X	X	X	X	X	X	X	X

PRECISION DRILL ROD Close Tolerance, Precision Fit

Typical Diameter Tolerances

.124" Round and Smaller	(+/- .0003")
.125" Round to .499" Round	(+/- .0005")
.500" Round to 2" Round	(+/- .001")

Lengths Available

18" and 36" Lengths
Call for availability on lengths up to 144" long on special sizes.

Sizes Available*

1/16"	5/16"	9/16"	13/16"	1-1/16"	1-5/16"	1-9/16"	1-13/16"
1/8"	3/8"	5/8"	7/8"	1-1/8"	1-3/8"	1-5/8"	1-7/8"
3/16"	7/16"	11/16"	15/16"	1-3/16"	1-7/16"	1-11/16"	1-15/16"
1/4"	1/2"	3/4"	1"	1-1/4"	1-1/2"	1-3/4"	2"

* For **METRIC** availability, please call our call our office for further details.